

SOPRANO WM X

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
SOPRANO WM X 15	14W	1450 Lm	104 lm/W	306 x 28 x 100 mm	SWMX15
SOPRANO WM X 25	25W	2640 Lm	106 lm/W	551 x 28 x 100 mm	SWMX25
SOPRANO WM X 50	48W	5290 Lm	110 lm/W	1091 x 28 x 100 mm	SWMX50
SOPRANO WM X 80	74W	7930 Lm	107 lm/W	1631 x 28 x 100 mm	SWMX80
SOPRANO WM X 110	97W	10570 Lm	109 lm/W	2176 x 28 x 100 mm	SWMX110

*Values are given for colour temperature of 4000K, OPQ diffuser, CRI 80 and may vary for other options


MATERIALS

CASING - electrostatically painted aluminum; standard colour - grey

DIFFUSER - OPQ-Opal/Polycarbonate, PAR-Parabolic Louvers/Prismatic plastic

INSTALLATION

Wall mounted



ORDER CODE

COLOUR TEMPERATURE

3000K	3K
4000K	4K

DRIVERTYPE

Standard	ST
Dimming - DALI	DL

DIFFUSER

Opal	OPQ
Parabolic Louvers	PAR

CASING COLOUR

Grey	GR
White	WH
Black	BL
Custom	RAL

CRI

≥ 90	C90
------	-----

Order code example: **SWMX15-4K-ST-OPQ-GR**