



## INDIC

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	COLOUR TEMPERATURE	ORDER REFERENCE
INDI C 25	25W	2510 Lm	100 lm/W	587 x 57 x 75 mm	3000K	INDC25
INDI C 25	25W	2560 Lm	102 lm/W	587 x 57 x 75 mm	4000K	INDC25

\*Values are given for HEX diffuser, CRI 80 and may vary for other options

### MATERIALS

CASING - electrostatically painted aluminium; standard colour - grey

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA

### INSTALLATION

Surface mounted

Suspended

### FIXINGS

	INFO	CODE
End Cap	Single/Metal*	INDI-ENDCAP
	Single/PC	INDI-ENDCAPS-S
Joints	Inline	INDI-JOINT-I
	Surface Mounting Bracket*	INDI-JOINT-S
	Corner 90°*	INDI-JOINT-C
Suspension Kit	Simple INOX	ZLISS-INOX
	Electrical*	ZLISS-SUSP

\*Any RAL colour option available. Order example: **INDI-ENDCAP-GR**



### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVER TYPE

Standard ST

Dimming - DALI DL

#### DIFFUSER

Micro-prismatic HEX

Opal OPQ

#### CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL

#### CRI

≥ 90 C90

Order code example: **INDC25-4K-ST-HEX-GR**