



RESTO

L80 B10 > 53 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION (OPQ/HEX/PAR)	LUMEN OUTPUT (OPQ/HEX/PAR)*	EFFICACY (OPQ/HEX/PAR)*	PRODUCT SIZE	ORDER REFERENCE
RESTO 35	31/31/30W	3410/4030/3860 Lm	110/130/129 lm/W	1145 x 125 x 52 mm	REST35
RESTO 40	37/37/38W	4240/4750/4830 Lm	115/128/127 lm/W	1435 x 125 x 52 mm	REST40

*Values are given for colour temperature of 4000K, OPQ diffuser, CRI 80 and may vary for other options

MATERIALS

CASING - powder painted steel sheet body; standard colour - white

DIFFUSER - HEX-Micro-prismatic/PMMA, OPQ-Opal/Polycarbonate, PAR-Parabolic Louvers/Aluminium

INSTALLATION

Surface mounted


Suspended

FIXINGS

	INFO	CODE
End Cap*	Single**	REST-ENDCAP
Joint*	Linear	REST-JOINT-L
Suspension kit	Simple INOX	ZLISS-INOX
	Simple INOX Y	ZLISS-INOX-Y
	Electrical **	ZLISS-SUSP
	Electrical Y**	ZLISS-SUSP-Y

*Only for PARS version

Any RAL colour option available. Order example: **ZLISS-SUSP-GR



ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

DIFFUSER

Micro-prismatic HEX

Opal OPQ

Parabolic Louvers Satin PARS

CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL

EMERGENCY MODULE

3 hr EM

CRI

≥ 90 C90

Order code example: **REST35-4K-ST-OPQ-WH**