



LITHIUM LITE SM IP

L80 B10 > 64 000h | SDCM 3 | LLMF 86% | CRI 80-90+

| PRODUCT NAME | POWER CONSUMPTION | LUMEN OUTPUT* | EFFICACY* | PRODUCT SIZE | ORDER REFERENCE |
|-----------------------|-------------------|---------------|-----------|----------------|-----------------|
| LITHIUM LITE SM IP 10 | 10W | 1160 Lm | 116 lm/W | Ø 245 x 188 mm | LISP10 |
| LITHIUM LITE SM IP 15 | 15W | 1590 Lm | 106 lm/W | Ø 245 x 188 mm | LISP15 |
| LITHIUM LITE SM IP 20 | 19W | 2030 Lm | 107 lm/W | Ø 245 x 188 mm | LISP20 |
| LITHIUM LITE SM IP 30 | 28W | 2750 Lm | 98 lm/W | Ø 245 x 188 mm | LISP30 |

* Values are given for colour temperature of 4000K, C80 and may vary for other options

MATERIALS

CASING - powder painted aluminium; standard colour - white

DIFFUSER - tempered glass

REFLECTOR - aluminium with a purity of 99,85%

INSTALLATION

Surface mounted

Suspended

ACCESSORIES

| | INFO | CODE |
|-----------------|---------------|-----------|
| Suspension Kit* | 1,5m 5x0,75mm | LITH-SUSP |

*Any RAL colour option available



ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

CASING COLOUR

White WH

Grey GR

Black BL

Custom RAL

CRI

≥ 80 C80

≥ 90 C90

Order code example: **LISP30-4K-DL-WH-C80**