

CELTA

L80 B10 > 100 000h | SDCM 3 | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT (OPQ/HEX/ PAR 65°/PAR 80°)*	EFFICACY (OPQ/HEX/ PAR 65°/PAR 80°)*	PRODUCT SIZE	ORDER REFERENCE
CELTA 20	15W	1850/1890/2170/2110 Lm	123/126/145/141 lm/W	560 x 43 x 54 mm	CELT20
CELTA 30	21W	2780/2830/3250/3170 Lm	132/135/155/151 lm/W	840 x 43 x 54 mm	CELT30
CELTA 40	28W	3710/3770/4340/4220 Lm	133/135/155/151 lm/W	1120 x 43 x 54 mm	CELT40
CELTA 50	35W	4640/4720/5420/5280 Lm	133/135/155/151 lm/W	1400 x 43 x 54 mm	CELT50
CELTA 60	42W	5570/5660/6510/6330 Lm	133/135/155/151 lm/W	1680 x 43 x 54 mm	CELT60
CELTA 70	48W	6500/6600/7590/7390 Lm	135/138/158/154 lm/W	1960 x 43 x 54 mm	CELT70
CELTA 80	55W	7420/7540/8670/8440 Lm	135/137/158/153 lm/W	2240 x 43 x 54 mm	CELT80

*Values are given for colour temperature of 4000K, CRI 80 and may variate for other options

MATERIALS


CASING - electrostatically painted aluminium; standard colour - grey

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA, PAR-Parabolic Louvers/Polucarbonate

INSTALLATION

Surface mounted

Suspended





CELTA

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
DIFFUSER	
Opal	OPQ
Micro-prismatic	HEX
Micro-prismatic with flex layer	HEXP
Parabolic Louvers 65° beam angle	PAR65
Parabolic Louvers 80° beam angle	PAR80
PARABOLIC COLOUR*	
White	WH
Black	BL
Metalized	M
Custom	RAL
CASING COLOUR	
Grey	GR
White	WH
Black	BL
Custom	RAL
EMERGENCY MODULE**	
3 hr	EM
ADD-ONS	
Motion Sensor	MS
CRI	
≥ 90	C90
THROUGH WIRING***	
5-phase through wiring	TW5

*In PAR versions only

**Available from lengths 1120mm and above

***Available on request

Order code example:

CELT40-4K-ST-HEX-GR-EM-MS

FIXINGS

	INFO	CODE
End Cap	Single/Metal*	CELT-ENDCAP
	Inline	CELT-JOINT-I
Joints	T-joint*	CELT-JOINT-T
	Corner 90°*	CELT-JOINT-C
	Plus joint*	CELT-JOINT-PLUS
Suspension Kit	Simple INOX	ZLISS-INOX
	Electrical*	ZLISS-SUSP
Blank infill	560 mm*	CELT-INFL-560
	840 mm*	CELT-INFL-840
	1120 mm*	CELT-INFL-1120
	1400 mm*	CELT-INFL-1400
	1680 mm*	CELT-INFL-1680

*Any RAL colour option available.

Order example: **CELT-ENDCAP-BL**

