



LITHIUM IP

L90 B10 > 60 000h | SDCM 3 | LLMF 91% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE		ORDER REFERENCE
LITHIUM IP 15	15W	1720 Lm	115 lm/W	Ø 245 x 130 mm		LIIP15
LITHIUM IP 20	21W	2380 Lm	113 lm/W	Ø 245 x 130 mm	212 mm	LIIP20
LITHIUM IP 30	29W	3190 Lm	110 lm/W	Ø 245 x 130 mm		LIIP30

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - powder painted aluminium; standard colour - white

DIFFUSER - transparent tempered glass

REFLECTOR - polished and faceted aluminium with a mirror finish

INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

CASING COLOUR

White WH

Grey GR

Black BL



Custom RAL

EMERGENCY MODULE

3 hr EM

CRI

≥ 90 C90



Order code example: **LIIP20-4K-DL-WH**