



## CAPPUCCINO

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
CAPPUCCINO 20	13W	1870 Lm	144 lm/W	565 x 161 x 60 mm	CAPP20
CAPPUCCINO 40	26W	3750 Lm	144 lm/W	1060 x 161 x 60 mm	CAPP40
CAPPUCCINO 55	39W	5620 Lm	144 lm/W	1555 x 161 x 60 mm	CAPP55

\*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

### MATERIALS

CASING - powder painted steel

DIFFUSER - OPQ-Opal/Polycarbonate

### INSTALLATION

Surface mounted

Suspended

Wall mounted

### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVER TYPE

Standard ST

Dimming - DALI DL

#### EMERGENCY MODULE\*

3 hr EM


#### CRI

≥ 90 C90

\*Available in CAPP40 and CAPP55 on request

### FIXINGS

	INFO	CODE
Suspension Kit	Simple INOX	ZLISS-INOX
	Electrical	ZLISS-SUSP-WH



Order code example: **CAPP40-4K-ST**