



## LITHIUM MINI

L90 B10 > 60 000h | SDCM 3 | LLMF 91% | CRI 80+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE		ORDER REFERENCE
LITHIUM MINI S 5	6W	690 Lm	115 lm/W	Ø 100 x 75 mm	90 mm	LIMS5
LITHIUM MINI S 10	9W	1130 Lm	126 lm/W	Ø 100 x 75 mm		LIMS10
LITHIUM MINI M 15	13W	1685 Lm	130 lm/W	Ø 140 x 90 mm	130 mm	LIMM15
LITHIUM MINI M 30	26W	3100 Lm	119 lm/W	Ø 140 x 90 mm		LIMM30
LITHIUM MINI L 25	18W	2330 Lm	129 lm/W	Ø 185 x 112 mm	170 mm	LIML25
LITHIUM MINI L 35	33W	3750 Lm	114 lm/W	Ø 185 x 112 mm		LIML35
LITHIUM MINI L 40	40W	4025 Lm	101 lm/W	Ø 185 x 112 mm		LIML40

\*Values are given for colour temperature of 4000K, reflector RWH and may vary for other options

### MATERIALS

CASING - powder painted aluminum; standard colour - white

DIFFUSER - transparent structural plastic

REFLECTOR - plastic reflector white, black or metalized colour

### INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard

### INFO

Remote emergency pack available

### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVERTYPE

Standard ST

Dimming - DALI DL

#### REFLECTOR

White RWH

Black RBL

Metallic RMT

#### CASING COLOUR

White WH

Black BL

Grey GR

Custom RAL



Order code example: **LIMM30-4K-DL-RWH-WH**