zliss

CE | RoHS | IP65 | RAL | MADE IN EU

WALLY

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
WALLY 5	3W	250 Lm	83 lm/W	180 x 180 x 80 mm	WALL5
WALLY 10	5W	500 Lm	100 lm/W	280 x 120 x 80 mm	WALL10
WALLY 20	10W	1000 Lm	100 lm/W	480 x 120 x 80 mm	WALL20

*Values are given for colour temperature of 4000K, CRI 80 and may variate for other options

MATERIALS

CASING - powder painted steel sheet body, aluminium frame made with aluminium; standard colour - white

DIFFUSER - clear polycarbonate

INSTALLATION

Recessed

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI*	DL
CASING COLOUR	
White	WH
Anthracite Grey	AG
Black	BL
Custom	RAL
CRI	
≥ 90	C90

*Available in WALL10 and WALL20 on request

Order code example: **WALL20-4K-ST-WH**