



on request

## FLYLINE TRIMLESS

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
FLYLINE TRIMLESS 15	13W	1480 Lm	114 lm/W	545 x 57 x 75 mm	FLYT15
FLYLINE TRIMLESS 30	25W	2955 Lm	118 lm/W	1085 x 57 x 75 mm	FLYT30
FLYLINE TRIMLESS 45	36W	4425 Lm	123 lm/W	1625 x 57 x 75 mm	FLYT45
FLYLINE TRIMLESS 60	48W	5900 Lm	123 lm/W	2170 x 57 x 75 mm	FLYT60

\*Values are given for colour temperature of 4000K, OPQ diffuser, CRI 80 and may vary for other options

### FIXINGS

	INFO	CODE
End Cap	Single*	FLYT-ENDCAP
Joint	Linear	FLYT-JOINT-L
Template	Trimless Recessed installation template	FLYL-TEMP

\*Any RAL colour option available. Order example: **FLYT-ENDCAP-WH**

### MATERIALS

CASING - electrostatically painted trimless aluminium;  
standard colour - white

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA

### INSTALLATION

Into plaster-cardboard ceiling

### ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL

### DIFFUSER

Micro-prismatic	HEX
Opal	OPQ

### CASING COLOUR

Grey	GR
White	WH
Black	BL
Custom	RAL

### EMERGENCY MODULE\*

3 hr	EM
------	----

### ADD-ONS

Motion Sensor	MS
---------------	----

### CRI

≥ 90	C90
------	-----

### THROUGH WIRING\*\*

5-phase through wiring	TW5
------------------------	-----

\*Remote EM pack on FLYT15 & FLYT30 only

\*\*Available on request

Order code example: **FLYT15-4K-ST-OPQ-GR**

