



## LITHIUM MINI SM

L90 B10 > 60 000h | SDCM 3 | CRI 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
LITHIUM MINI SM S 5	6W	665 Lm	111 lm/W	Ø 82 x 106 mm	LSMS5
LITHIUM MINI SM S 10	9W	1085 Lm	121 lm/W	Ø 82 x 106 mm	LSMS10
LITHIUM MINI SM M 15	13W	1620 Lm	125 lm/W	Ø 115 x 120 mm	LSMM15
LITHIUM MINI SM M 30	26W	2980 Lm	115 lm/W	Ø 115 x 120 mm	LSMM30
LITHIUM MINI SM L 20	18W	2240 Lm	124 lm/W	Ø 149 x 143 mm	LSML20
LITHIUM MINI SM L 35	33W	3600 Lm	109 lm/W	Ø 149 x 143 mm	LSML35
LITHIUM MINI SM L 40	40W	3865 Lm	97 lm/W	Ø 149 x 143 mm	LSML40

\*Values are given for colour temperature of 4000K, RBL and may vary for other options

### MATERIALS

CASING - powder painted aluminum; standard colour - white

DIFFUSER - transparent structural plastic

REFLECTOR - plastic

### INSTALLATION

Surface mounted

Suspended only in Ø 149 mm versions

### INFO

Remote emergency pack available

### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVERTYPE

Standard ST

Dimming - DALI\* DL

#### REFLECTOR COLOUR

White RWH

Black RBL

Metallic RMT

#### CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL

\*Available in LSMM15, LSMM30, LSML20, LSML35 and LSML40

Order code example: **LSMM30-4K-DL-RBL-WH**

