



FLYLINE TRIMLESS C

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT	EFFICACY	PRODUCT SIZE	COLOUR TEMPERATURE	ORDER REFERENCE
FLYLINE TRIMLESS C 30	25W	2790 Lm	112 lm/W	576 x 57 x 75 mm	3000K	FTRC30
FLYLINE TRIMLESS C 30	25W	2835 Lm	113 lm/W	576 x 57 x 75 mm	4000K	FTRC30

*Values are given for OPQ diffuser, CRI 80 and may vary for other options

MATERIALS

CASING - electrostatically painted aluminium; standard colour - white

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA

INSTALLATION

Into plaster-cardboard ceiling

FIXINGS

	INFO	CODE
End Cap	Single*	FLYT-ENDCAP
Joint	Linear	FLYT-JOINT-L

*Any RAL colour option available. Order example: **FLYT-ENDCAP-WH**

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
DIFFUSER	
Micro-prismatic	HEX
Opal	OPQ
CASING COLOUR	
Grey	GR
White	WH
Black	BL
Custom	RAL
CRI	
≥ 90	C90



Order code example: **FTRC30-4K-ST-OPQ-WH**