



## IDRO

L90 B10 > 100 000h | SDCM 3 | CRI 70+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
IDRO 45	34W	4451 Lm	131 lm/W	425 x 425 x 816 mm	IDRO45
IDRO 55	44W	5557 Lm	126 lm/W	425 x 425 x 816 mm	IDRO55
IDRO 65	51W	6677 Lm	131 lm/W	425 x 425 x 816 mm	IDRO65
IDRO 85	66W	8335 Lm	126 lm/W	425 x 425 x 816 mm	IDRO85

\*Values are given for colour temperature of 4000K, and may vary for other options

### MATERIALS

CASING - aluminium;  
standard colour - black grey

DIFFUSER - lenses, tempered glass,  
impact resistant

### INSTALLATION

With three screws on poles Ø60mm

### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

5000K 5K

#### DRIVER TYPE

Standard ST

Dimming - DALI DL

Autonomous  
two-level dimming ADIM

#### OPTICS

Symmetrical SM

Asymmetric beam SM1 ASM1

Asymmetric beam SS1 ASS1

#### CASING COLOUR

Grey GR

Black BL

White WH

Custom RAL

#### ADD-ONS

PCA Sensor PCA

Order code example: **IDRO45-4K-ST-SM-GR**