



# SOLIS RM IP65

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

| PRODUCT NAME         | POWER CONSUMPTION | LUMEN OUTPUT* | EFFICACY* | PRODUCT SIZE       | ORDER REFERENCE |
|----------------------|-------------------|---------------|-----------|--------------------|-----------------|
| SOLIS RM IP65 L 50   | 43W               | 5100 lm       | 119 lm/W  | 595 x 595 x 90 mm  | SLIP50          |
| SOLIS RM IP65 XL 50  | 43W               | 4910 lm       | 114 lm/W  | 1195 x 295 x 90 mm | SXIP50          |
| SOLIS RM IP65 L 115  | 100W              | 11470 lm      | 115 lm/W  | 595 x 595 x 90 mm  | SLIP115         |
| SOLIS RM IP65 XL 100 | 84W               | 9820 lm       | 117 lm/W  | 1195 x 595 x 90 mm | SLIP100         |

\* Values are given for colour temperature of 4000K, OPQ diffuser, CRI 80 and may vary for other options

## MATERIALS

CASING - powder painted steel; standard colour - white

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA, PAR-Parabolic Louvers/Aluminium, MGL-SH MAT/Matte tempered glass

## INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard

## ORDER CODE

### COLOUR TEMPERATURE

3000K 3K

4000K 4K

### DRIVER TYPE

Standard ST

Dimming - DALI DL

### DIFFUSER

Micro-prismatic HEX

Opal OPQ

Parabolic Louvers PAR

Matte tempered glass (SH MAT) MGL

### CASING COLOUR

White WH

Grey GR

Black BL

Custom RAL

### EMERGENCY MODULE

3 hr EM

### CRI

≥ 90 C90



Order code example: **SLIP50-4K-ST-OPQ-WH-EM**