



GEO CR MAX

L80 B10 > 60 000h | SDCM 3 | LLMF 86% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
GEO CR MAX 14	146W	15900 Lm	109 lm/W	Ø 1400 x 62 mm	GCMX14
GEO CR MAX 16	166W	18000 Lm	108 lm/W	Ø 1600 x 62 mm	GCMX16
GEO CR MAX 21	220W	24200 Lm	110 lm/W	Ø 2100 x 62 mm	GCMX21
GEO CR MAX 28	300W	33000 Lm	110 lm/W	Ø 2800 x 62 mm	GCMX28
GEO CR MAX 40	429W	47000 Lm	110 lm/W	Ø 4000 x 62 mm	GCMX40
GEO CR MAX 53	574W	62800 Lm	109 lm/W	Ø 5300 x 62 mm	GCMX53

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - powder painted aluminum profile; standard colour - grey

DIFFUSER - OPQ-Opal/Polycarbonate

INSTALLATION

Suspended (suspensions in set)

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL

EMERGENCY MODULE*

3 hr EM

CRI

≥ 90 C90

*Available on request

Order code example: **GCMX14-4K-ST-BL**

