



FLYLINE

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

on request

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
FLYLINE 15	13W	1610 Lm	124 lm/W	545 x 73 x 75 mm	FLYL15
FLYLINE 30	25W	3215 Lm	129 lm/W	1085 x 73 x 75 mm	FLYL30
FLYLINE 45	36W	4825 Lm	134 lm/W	1625 x 73 x 75 mm	FLYL45
FLYLINE 60	48W	5900 Lm	123 lm/W	2170 x 73 x 75 mm	FLYL60

*Values are given for colour temperature of 4000K, HEX diffuser, CRI 80 and may vary for other options

MATERIALS

CASING - electrostatically painted aluminium; standard colour - grey

DIFFUSER - HEX-Micro-prismatic/PMMA, OPQ-Opal/Polycarbonate

FIXINGS

	INFO	CODE
End Cap	Single*	FLYL-ENDCAP
Joints	Inline Recessed	FLYL-JOINT-I
	Corner 90°*	FLYL-JOINT-C

*Any RAL colour option available.
Order example: **FLYL-ENDCAP-GR**

INSTALLATION

Recessed into plaster-cardboard



ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL

DIFFUSER	
Micro-prismatic	HEX
Opal	OPQ
CASING COLOUR	
Grey	GR
White	WH
Black	BL
Custom	RAL
EMERGENCY MODULE*	
3 hr	EM
ADD-ONS	
Motion Sensor	MS
CRI	
≥ 90	C90
THROUGH WIRING**	
5-phase through wiring	TW5

*Remote EM pack on FLYL15 & FLYL30 only
**Available on request

Order code example: **FLYL45-4K-ST-HEX-GR-EM**