



PISTON TRACK

L90 B10 > 60 000h | SDCM 3 | LLMF 91% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
PISTON TRACK 15	15W	1470 Lm	98 lm/W	Ø 80 x 200 mm	PSTR15
PISTON TRACK 20	21W	2030 Lm	97 lm/W	Ø 80 x 200 mm	PSTR20
PISTON TRACK 25	29W	2640 Lm	91 lm/W	Ø 80 x 200 mm	PSTR25

*Values are given for colour temperature of 4000K, 50° beam angle, CRI 80 and may vary for other options

MATERIALS

CASING - electrostatically painted aluminium; standard colour - anthracite grey

REFLECTOR - polycarbonate with mirror finish

INSTALLATION

Electrical track

ACCESSORIES

INFO	CODE
400 mm	PIST400
Empty Module*	PIST800
1200 mm	PIST1200

*Any RAL colour option available. Order example: **PIST800-AG**



ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVERTYPE	
Standard	ST
Dimming - DALI	DL
CASING COLOUR	
Anthracite Grey	AG
White	WH
Black	BL
Custom	RAL
BEAM ANGLE	
30 °	30
50 °	50
70 °	70
CRI	
≥ 90	C90

Order code example: **PSTR15-4K-ST-BL-70**