



SOLIS IM

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION*	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	DIFFUSER	ORDER REFERENCE
SOLIS IM S 40	40W	4350 Lm	109 lm/W	595 x 595 x 73 mm	HEX	SIMS40
SOLIS IM S 40	36W	4050 Lm	113 lm/W	595 x 595 x 73 mm	PARW	SIMS40
SOLIS IM S 40	36W	3940 Lm	109 lm/W	595 x 595 x 73 mm	PARM	SIMS40
SOLIS IM L 40	44W	4700 Lm	107 lm/W	1195 x 295 x 73 mm	HEX	SIML40
SOLIS IM L 40	39W	4230 Lm	108 lm/W	1195 x 295 x 73 mm	PARW	SIML40
SOLIS IM L 40	39W	4100 Lm	105 lm/W	1195 x 295 x 73 mm	PARM	SIML40

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - powder painted steel sheet and aluminium frame in white colour

DIFFUSER - HEX-Micro-prismatic/PMMA, PAR-Parabolic Louvers/Aluminium

INSTALLATION

Recessed into the modular ceiling



ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
DIFFUSER	
Micro-prismatic	HEX
Parabolic Louvers-white	PARW
Parabolic Louvers-metallized	PARM
EMERGENCY MODULE*	
3 hr	EM
CRI	
≥ 90	C90

*Only available in SIMS40 HEX and PARW on request

Order code example: **SIMS40-4K-DL-HEX**