

INDI X WM

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
INDI X WM 20	25W	2390 Lm	96 lm/W	545 x 60 x 75 mm	INXW20
INDI X WM 40	48W	4780 Lm	100 lm/W	1085 x 60 x 75 mm	INXW40
INDI X WM 60	68W	7170 Lm	105 lm/W	1625 x 60 x 75 mm	INXW60
INDI X WM 80	90W	9560 Lm	106 lm/W	2165 x 60 x 75 mm	INXW80

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - electrostatically painted aluminium; standard colour - grey

DIFFUSER - OPQ-Opal/Polycarbonate



INSTALLATION

Wall mounted

FIXINGS

	INFO	CODE
End Cap	Single/Metal*	INDI-ENDCAP
	Single/PC	INDI-ENDCAP-S
Joints	Inline	INDI-JOINT-I
	Corner 90°*	INDI-JOINT-C

*Any RAL colour option available. Order example: **INDI-ENDCAP-GR**



ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
CASING COLOUR	
Grey	GR
White	WH
Black	BL
Custom	RAL
EMERGENCY MODULE*	
3 hr	EM
CRI	
≥ 90	C90

THROUGH WIRING**

5-phase through wiring TW5

*Only available in INXW60 and INXW80 on request

**Available on request

Order code example: **INXW20-4K-ST-GR**