



TRACKER

L90 B10 > 60 000h | SDCM 3 | LLMF 91% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	BEAM ANGLES	ORDER REFERENCE
TRACKER S 10	9W	950 Lm	106 lm/W	Ø 65 x 150 mm	50 °	TRCS10
TRACKER S 15	13W	1700 Lm	131 lm/W	Ø 65 x 150 mm	50 °	TRCS15
TRACKER M 20	16W	2120 Lm	133 lm/W	Ø 80 x 170 mm	55 °	TRCM20
TRACKER M 25	19W	2520 Lm	133 lm/W	Ø 80 x 170 mm	55 °	TRCM25
TRACKER M 35	26W	3330 Lm	128lm/W	Ø 80 x 170 mm	55 °	TRCM35
TRACKER L 35	26W	3530 Lm	136 lm/W	Ø 100 x 200 mm	55 °	TRCL35
TRACKER L 45	34W	4360 Lm	128 lm/W	Ø 100 x 200 mm	55 °	TRCL45

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - electrostatically painted aluminium; colour - white and black

REFLECTOR - High Gloss Mirror Finish

INFO - LED COB Chip; It can rotate up to 350° with respect to the vertical axis and pivot up to 90° upwards

INSTALLATION

Electrical tracks

ON REQUEST

Versions with colour light temperature adjusted to subject illumination (museum exhibitions, meat, vegetables, fruits, fish)



ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

CASING COLOR

White WH

Black BL

OPTICS WITH BEAM ANGLES

Narrow (15°, 18°, 19°) N...

Medium (26°, 36°, 40°) M...

Wide (50° & 55°) W...

CASING COLOR

≥ 90 C90

Order code example: **TRCM20-4K-ST-BL-W55**