



KNAPP

L80 B10 > 50 000h | SDCM 3 | CRI 80+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
KNAPP S 5	5W	431 Lm	86 lm/W	430 x 115 x 105 mm	KPPS5
KNAPP S 10	7W	529 Lm	76 lm/W	430 x 115 x 105 mm	KPPS10
KNAPP M 5	9W	754 Lm	84 lm/W	630 x 115 x 105 mm	KPPM5
KNAPP M 10	11W	926 Lm	84 lm/W	630 x 115 x 105 mm	KPPM10
KNAPP L 10	17W	1401 Lm	82 lm/W	1050 x 115 x 105 mm	KPPL10
KNAPP L 15	20W	1721 Lm	86 lm/W	1050 x 115 x 105 mm	KPPL15

*Values are given for colour temperature of 4000K and may vary for other options

MATERIALS

CASING - stainless steel; colour - stainless-steel, brushed

Diffuser - frosted tempered glass, impact resistant

FIXINGS

	INFO	CODE
Power supply connector I	IP68 2 x 3 x 2.5 mm	KNAPP-I
Power supply connector T	IP68 3 x 3 x 2.5 mm	KNAPP-T



INSTALLATION

Recessed

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVERTYPE	
Standard	ST
Dimming - DALI	DL

Order code example: **KPPS10-4K-ST**