



PISTON SM

L90 B10 > 60 000h | SDCM 3 | LLMF 91% | CRI 80+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
PISTON SM S 15	15W	1470 Lm	98 lm/W	Ø 80 x 140 mm	PSSM15
PISTON SM S 20	21W	2030 Lm	97 lm/W	Ø 80 x 140 mm	PSSM20
PISTON SM M 15	15W	1470 Lm	98 lm/W	Ø 80 x 200 mm	PSMM15
PISTON SM M 20	21W	2030 Lm	97 lm/W	Ø 80 x 200 mm	PSMM20
PISTON SM M 25	29W	2640 Lm	91 lm/W	Ø 80 x 200 mm	PSMM25

*Values are given for colour temperature of 4000K, 50° beam angle, IP20 and may vary for other options

MATERIALS

CASING - electrostatically painted aluminium; standard colour - anthracite grey

REFLECTOR - metallised plastic

INSTALLATION

Ceiling mounted

ORDER CODE

COLOUR TEMPERATURE

3000K	3K
4000K	4K

DRIVER TYPE

Standard	ST
Dimming - DALI	DL

CASING COLOUR

Anthracite Grey	AG
White	WH
Black	BL
Custom	RAL

BEAM ANGLE

30°	30
50°	50
70°	70

IP RATING

IP20	IP20
IP44	IP44

Order code example: **PSMM15-4K-ST-BL-50-IP20**

