



## LITHIUM LITE

L80 B10 > 64 000h | SDCM 3 | LLMF 86% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE		ORDER REFERENCE
LITHIUM LITE S 10	10W	1120 Lm	112 lm/W	Ø 195 x 106 mm	180 mm	LLIS10
LITHIUM LITE S 15	15W	1530 Lm	102 lm/W	Ø 195 x 106 mm		LLIS15
LITHIUM LITE M 15	15W	1580 Lm	105 lm/W	Ø 235 x 106 mm	220 mm	LLIM15
LITHIUM LITE M 20	19W	2000 Lm	105 lm/W	Ø 235 x 106 mm		LLIM20
LITHIUM LITE M 30	28W	2710 Lm	97 lm/W	Ø 235 x 106 mm		LLIM30

\*Values are given for colour temperature of 4000K, reflector RM, CRI 80 and may vary for other options

### MATERIALS

CASING - powder painted aluminium

DIFFUSER - prismatic plastic

REFLECTOR - polished aluminum with a purity of 99,85%

### INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard

### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVER TYPE

Standard ST

Dimming - DALI DL

#### REFLECTOR

Matt RM

Metallized (silver) RF

#### CASING COLOUR

White WH

Grey GR

Black BL

Custom RAL

#### EMERGENCY MODULE

3 hr EM

#### CRI

≥ 90 C90



Order code example: **LLIM20-4K-DL-RM-WH**