



on request

INDI TRACK

L90 B10 > 60 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION (OPQ/HEX/PAR)	LUMEN OUTPUT (OPQ/HEX/PAR)*	EFFICACY (OPQ/HEX/PAR)*	PRODUCT SIZE	ORDER REFERENCE
INDI TRACK 10	13/13/14W	1130/1230/1660 Lm	87/95/119 lm/W	545 x 57 x 75 mm	ITRK10
INDI TRACK 25	25/25/27W	2380/2560/3320 Lm	95/102/123 lm/W	1085 x 57 x 75 mm	ITRK25
INDI TRACK 40	36/36/40W	3680/3940/4980 Lm	102/109/125 lm/W	1625 x 57 x 75 mm	ITRK40

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - electrostatically painted aluminum; standard colour -grey

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA, PAR-Parabolic Louvers/Aluminium

INSTALLATION

Electrical track

FIXINGS

	INFO	CODE
Suspension Kit	Simple INOX	ZLISS-INOX
	Electrical*	ZLISS-SUSP
Upper Masking Cover (Blank infill)	545 mm*	INDI15-BACK
	1085 mm*	INDI25-BACK
	1625 mm*	INDI40-BACK

*Any RAL colour option available. Order example: **ZLISS-SUSP-GR**



ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
DIFFUSER	
Opal	OPQ
Micro-prismatic	HEX
Parabolic Louvers	PAR
CASING COLOUR	
Grey	GR
Black	BL
White	WH
Custom	RAL
CRI	
≥ 90	C90

Order code example: **ITRK10-4K-DL-HEX-WH**