



on request

ARGO

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	DIFFUSER	PRODUCT SIZE	ORDER REFERENCE
ARGO 20	16W	1750 Lm	109 lm/W	HEX/OPQ	Ø 320 x 66 mm	ARGO20
ARGO 40	37W	3870 Lm	105 lm/W	HEX/OPQ	Ø 440 x 69 mm	ARGO40
ARGO 45	37W	4150 Lm	112 lm/W	HEX/OPQ	Ø 520 x 69 mm	ARGO45
ARGO 50	37W	4530 Lm	122 lm/W	HEX/OPQ	Ø 630 x 110 mm	ARGO50
ARGO 65	57W	6370 Lm	112 lm/W	OPQ	Ø 800 x 110 mm	ARGO65
ARGO 120	100W	12250 Lm	123 lm/W	OPQ	Ø 1065 x 110 mm	ARGO120

*Values are given for colour temperature of 4000K, OPQ diffuser, CRI 80 and may vary for other options

MATERIALS

CASING - powder painted aluminium; standard colour - grey

BASE - steel sheet

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA

INSTALLATION

Surface mounted


Suspended

Recessed (additional mounting bracket required)

FIXINGS

	INFO	CODE
Suspension set*	1.5m	ARGO-SP
	Ø 320	ARGO20-RM
	Ø 440	ARGO40-RM
Recessed mounting kit	Ø 520	ARGO45-RM

*Any RAL colour option available. Order example: **ARGO-SP-GR**



ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

DIFFUSER

Micro-prismatic HEX

Opal OPQ

CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL

EMERGENCY MODULE*

3 hr EM

CRI

≥ 90 C90

*Available in ARGO40, ARGO65 and ARGO120

Order code example: **ARGO40-4K-ST-HEX-WH**