

## PISTON SQ

L90 B10 > 60 000h | SDCM 3 | LLMF 90% | CRI 80+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
PISTON SQ 15	14W	1650 Lm	118 lm/W	85 x 85 x 200 mm	PSSQ15
PISTON SQ 20	20W	2310 Lm	116 lm/W	85 x 85 x 200 mm	PSSQ20
PISTON SQ 25	27W	3090 Lm	114 lm/W	85 x 85 x 200 mm	PSSQ25

\*Values are given for colour temperature of 4000K, 50° beam angle and may vary for other options

### MATERIALS

CASING - electrostatically painted aluminium; standard colour - anthracite grey

REFLECTOR - High Gloss

INFO - LED COB Chip

### INSTALLATION

Suspended


### ACCESSORIES

INFO	CODE
400 mm	PSSQ400
Empty Module* 800 mm	PSSQ800
1200 mm	PSSQ1200

\*Any RAL colour option available. Order example: **PSSQ800-GR**

### ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVERTYPE	
Standard	ST
Dimming - DALI	DL
CASING COLOUR	
Anthracite Grey	AG
White	WH
Black	BL
Custom	RAL
BEAM ANGLE	
30°	30
50°	50
70°	70



Order code example: **PSSQ15-4K-ST-BL-70**