



TRACKER SM

L90 B10 > 60 000h | SDCM 3 | LLMF 91% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	BEAM ANGLES	ORDER REFERENCE
TRACKER SM S 10	9W	950 Lm	106 lm/W	Ø 65 x 150 mm	50 °	TRSS10
TRACKER SM S 15	13W	1700 Lm	131 lm/W	Ø 65 x 150 mm	50 °	TRSS15
TRACKER SM M 20	16W	2120 Lm	133 lm/W	Ø 80 x 170 mm	55 °	TRSM20
TRACKER SM M 25	19W	2520 Lm	133 lm/W	Ø 80 x 170 mm	55 °	TRSM25
TRACKER SM M 35	26W	3330 Lm	128 lm/W	Ø 80 x 170 mm	55 °	TRSM35
TRACKER SM L 35	26W	3530 Lm	136 lm/W	Ø 100 x 200 mm	55 °	TRSL35
TRACKER SM L 45	34W	4360 Lm	128 lm/W	Ø 100 x 200 mm	55 °	TRSL30

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - electrostatically painted aluminium; colour - white and black

REFLECTOR - High Gloss Mirror Finish

INFO - LED COB Chip

INSTALLATION


Surface mounted

ON REQUEST

Versions with colour light temperature adjusted to subject illumination (museum exhibitions, meat, vegetables, fruits, fish)

ACCESSORIES

	INFO	CODE
Shutter honeycomb	Black	TRAC-SHUT



ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVERTYPE	
Standard	ST
Dimming - DALI	DL
CASING COLOUR	
White	WH
Black	BL
OPTICS WITH BEAM ANGLES	
Narrow (15°,18°,19°)	N...
Medium (26°,36°,40°)	M...
Wide (50° & 55°)	W...
CRI	
≥ 90	C90

Order code example: **TRAS20-4K-ST-BL-W55**