



CE
RoHS
IP65
IK10
RAL
MADE IN EU
JANUS

L80 B10 > 50 000h | SDCM 3 | CRI 80+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
JANUS S 10	14W	1143 Lm	82 lm/W	Ø 265 x 90 mm	JANS10
JANUS M 10	11W	700 Lm	63 lm/W	Ø 265 x 100 mm	JANM10
JANUS L 10	14W	1164 Lm	83 lm/W	Ø 360 x 130 mm	JANL10
JANUS L 15	20W	1600 Lm	80 lm/W	Ø 360 x 130 mm	JANL15
JANUS L 20	24W	1956 Lm	82 lm/W	Ø 360 x 130 mm	JANL20
JANUS LOUVER 5	10W	582 Lm	58 lm/W	Ø 360 x 145 mm	JALO5
JANUS LOUVER 10	14W	800 Lm	57 lm/W	Ø 360 x 145 mm	JALO10

*Values are given for colour temperature of 4000K and may vary for other options

MATERIALS

CASING - aluminium; standard colour - dark grey

DIFFUSER - opal polycarbonate, UV stable, impact resistant

INSTALLATION

Surface mounted

Wall mounted

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

CASING COLOUR

Grey GR

Black BL

White WH

Custom RAL

EMERGENCY MODULE

3 hr EM

ADD-ONS*

Microwave sensor MW

*MW option is not compatible with LOUVER models and EM options



Order code example: **JANS10-4K-DL-GR-EM**