



COFFEX

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

| PRODUCT NAME | POWER CONSUMPTION (OPQ/PAR) | LUMEN OUTPUT (OPQ/PAR)* | EFFICACY (OPQ/PAR)* | PRODUCT SIZE | ORDER REFERENCE |
|--------------|-----------------------------|-------------------------|---------------------|--------------------|-----------------|
| COFFEX 15 | 17/14W | 1620/1650 Lm | 95/118 lm/W | 595 x 134 x 87 mm | COFF15 |
| COFFEX 30 | 31W | 3190 Lm | 103 lm/W | 595 x 134 x 87 mm | COFF30 |
| COFFEX 35 | 31/27W | 3600/3320 Lm | 116/123 lm/W | 1195 x 134 x 87 mm | COFF35 |
| COFFEX 65 | 60W | 6600 Lm | 110 lm/W | 1195 x 134 x 87 mm | COFF65 |

*Values are given for colour temperature of 4000K, CRI 80 and may vary for other options

MATERIALS

CASING - powder painted steel sheet; standard colour - white

DIFFUSER - OPQ-Opal/Polycarbonate, PAR-Parabolic Louvers/Aluminium

INSTALLATION



Into modular ceilings 600x600 with a visible supporting structure

ORDER CODE

| COLOUR TEMPERATURE | |
|--------------------|----|
| 3000K | 3K |
| 4000K | 4K |
| DRIVERTYPE | |
| Standard | ST |
| Dimming - DALI | DL |

| DIFFUSER | |
|--------------------|-----|
| Opal | OPQ |
| Parabolic Louvers* | PAR |
| CASING COLOUR | |
| White | WH |
| Grey | GR |
| Black | BL |
| Custom | RAL |
| EMERGENCY MODULE | |
| 3 hr | EM |
| CRI | |
| ≥ 90 | C90 |

*Only available in COFF15 and COFF35 on request



Order code example: **COFF30-4K-DL-QPQ-WH**