



TENNO

L80 B10 > 60 000h | SDCM 3 | CRI 80-95+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
TENNO 20	14W	1901 Lm	136 lm/W	175 x 175 x 119 mm	TENN20
TENNO 25	19W	2583 Lm	136 lm/W	175 x 175 x 119 mm	TENN25
TENNO 35	27W	3478 Lm	129 lm/W	175 x 175 x 119 mm	TENN35
TENNO 40	27W	3803 Lm	141 lm/W	350 x 175 x 119 mm	TENN40
TENNO 50	37W	5167 Lm	140 lm/W	350 x 175 x 119 mm	TENN50
TENNO 70	53W	6956 Lm	131 lm/W	350 x 175 x 119 mm	TENN70

*Values are given for colour temperature of 4000K, beam angle 40°, CRI 80 and may vary for other

MATERIALS

CASING - aluminium;
standard colour - white

DIFFUSER - clear PMMA

REFLECTOR - faceted aluminium

INSTALLATION

In ceilings with cut-out openings
(mounting brackets included)

ORDER CODE

COLOUR TEMPERATURE

2000K Meat*	2KM
2500K Bread*	2.5KB
2700K Natural***	2.7KN
3100K Meat&White*	3.1KMW
3000K	3K
3000K Vegetables**	3KV
3000K Natural***	3KN
3100K Fashion&White**	3.2KFW
3200K Fashion**	3.2KF
4000K	4K
4000K Natural***	4KN

DRIVER TYPE

Standard	ST
Dimming - DALI	DL

CASING COLOUR

Grey	GR
Black	BL
White	WH
Custom	RAL

BEAM ANGLE

24°	24
40°	40

CRI

≥ 80	C80
≥ 90	C90
≥ 95	C95

*Only available for CRI 80
** Only available for CRI 90
*** Only available for CRI 95

Order code example: **TENN20-4K-DL-WH-40-C80**

