



SOLIS P54

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT *	EFFICACY *	PRODUCT SIZE	ORDER REFERENCE
SOLIS P54 L 45	38W	4250 Lm	112 lm/W	595 x 595 x 80 mm	SP4L45
SOLIS P54 XL 45	43W	4520 Lm	105 lm/W	1195 x 295 x 80 mm	SP4X45

*Values are given for colour temperature of 4000K, OPQ diffuser, CRI 80 and may variate for other options

MATERIALS

CASING - powder painted steel; standard colour - white

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA

INSTALLATION

Recessed into plaster-cardboard ceiling

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
DIFFUSER	
Micro-prismatic	HEX
Opal	OPQ
CASING COLOUR	
White	WH
Grey	GR
Black	BL
Custom	RAL
EMERGENCY MODULE	
3 hr	EM
CRI	
≥ 90	C90
THROUGH WIRING*	
5-phase through wiring	TW5

*Available on request

Order code example: **SP4L45-4K-ST-OPQ-WH-EM**

