zliss

| CE | RoHS | IP65 | IK08 | RAL | MADE IN EU | | **BULA** |

L80 B50 > 50 000h │ **SDCM 6** │ **CRI 80+**

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
BULA 20	13W	1829 Lm	141 lm/W	319 x 165 x 265 mm	BULA20
BULA 25	18W	2535 Lm	141 lm/W	319 x 165 x 265 mm	BULA25
BULA 35	28W	3567 Lm	127 lm/W	319 x 165 x 265 mm	BULA35

*Values are given for colour temperature of 4000K and may variate for other options

MATERIALS

CASING - aluminium; standard colour - dark grey

DIFFUSER - lenses, frosted polycarbonate

INSTALLATION

Wall mounted

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
OPTICS	
Asymmetrical	AS
Symmetrical	SM
CASING COLOUR	
Grey	GR
Black	BL
White	WH
Custom	RAL
EMERGENCY MODULE	
3 hr	EM

Order code example: **BULA20-4K-DL-AS-GR-EM**