



LAGO

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	BEAM ANGLE	ORDER REFERENCE
LAGO 5	5W	450 Lm	90 lm/W	Ø 80 x 360 mm	360 °	LAGO5
LAGO 5	5W	275 Lm	55 lm/W	Ø 80 x 360 mm	90° + 90°	LAGO5
LAGO 5	5W	260 Lm	52 lm/W	Ø 80 x 360 mm	180 °	LAGO5
LAGO 10	10W	900 Lm	90 lm/W	Ø 80 x 360 mm	360 °	LAGO10
LAGO 10	10W	550 Lm	55 lm/W	Ø 80 x 360 mm	90° + 90°	LAGO10
LAGO 10	10W	520 Lm	52 lm/W	Ø 80 x 360 mm	180 °	LAGO10

*Values are given for colour temperature of 4000K and may vary for other options

MATERIALS

CASING - aluminum profile painted with paint resistant to external conditions; standard colour - graphite

DIFFUSER - transparent plastic

INSTALLATION

In-ground

FIXINGS

	INFO	CODE
Pole	LAGO pole, h=500 mm*	LAGO-P500
	LAGO pole, h=1000 mm*	LAGO-P1000
Base set	LAGO base for concrete	LAGO-BACN
	LAGO base to the ground	LAGO-BAGR

*Any RAL colour option available. Order example: **LAGO-P500-GR**

ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
CASING COLOUR	
Graphite	GR
White	WH
Black	BL
Custom	RAL
BEAM ANGLE	
360 °	360
90° + 90°	90
180 °	180
Custom	RAL

Order code example: **LAGO5-4K-ST-GR-360**